


NOTES:

COMPONENT IS ROHS\REACH COMPLIANT

Rating: 6A 250VAC/10A 125VAC T85 Contact Resistance: $\leq 50 \text{m}\Omega$ Insulation Resistance: $\geq 100 \text{M}\Omega$ Dielectric Intensity: $\geq 1500 \text{VAC/min}$

Life: ≥ 10000 Cycles

Hole Size: Scale: 2:1



Switch Type:



CONTACT SALES FOR CUSTOMISATION OPTIONS

ISSUE	DATE	SIG	REMARKS
1	06/08/2019	KN	SALES DRAWING



X X.X X.XX X.XXX ANGLES	0.50 0.25 0.10 0.05 0.25			
ALL DIMENSIONS IN MM				
THIRD ANGLE PROJECTION				
-				
	ALE DRAWING T PLEASE ASK			

TOLERANCES UNLESS OTHERWISE STATED

)	MATERIAL	CONTACT SALES
	COLOUR	CONTACT SALES
	SCALE	2:1 UNLESS SPECIFIED
	DRAWN	KN
	DATE	06/08/2019
	SHEET	1 OF 1

© GBK UK Limited

THESE DRAWINGS AND THE SPECIFICATIONS, AND THE DATA CONTAINED THEREIN ARE THE PROPERTY OF GBK UK LIMITED, ISSUED IN STRICT CONFIDENCE AND SHALL NOT WITHOUT PRIOR WRITTEN PERMISSION OF GBK UK LIMITED BE PRODUCED, COPIED OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT THE MANUFACTORE OR ARTICLES FOR GBK UK LIMITED

DESCRIPTION

ROCKER SWITCH WATERPROOF

DRAWING No.

50002-XXX-XXX